



94-465 Koaki Street
Waipahu, HI 96797

Phone: 866-402-2202

E-mail:

sales@pacificindustrialequipment.com

ELECTRIC 1000 SHIPYARD COMPRESSOR



Technical Information:

Capacity—990 cfm @ 125 PSIG

Maximum Operating Pressure—135 PSIG

Weight—8,000 lbs

Outlet Size—3" NPT

Dimensions—Facing control panel*

(L* x W x H) - 140" x 75" x 86"

Package Amp Draw Table—

460/3/60—269.5 Amps

575/3/60—215.7 Amps

Sound Level—80 dBA per CAGI-PNEUROP

200HP Electric Motor

Air Cooled Data:

Aftercooler CTD—15° F

Fan Air Flow—15,000 cfm

Standard Equipment:

- 2 Stage Rotary Screw Air Compressor
- Nema 4 Electrical Enclosure
- 460V Open Drip Proof High Efficiency Motor
- Star-Delta Starter / Soft Start
- Aircooled Aftercooler
- Intellisys Controller / With Weather Guard
- Phase Monitor / Voltage Monitor
- High Efficiency Coalescing Filter
- Coalescing / Particulate Filter
- 4 Way 6" x 9" Fork Truck Tubes
- 4 Point Certified Lifting / Military Spec
- Shipyard Lift Cage
- 1700 Series Camlock Electric Connections
- Instrument Quality Air