DRUM TOP VAC

TURN A 55 GALLON DRUM INTO THE BEST VACUUM YOU'LL EVER OWN



FOR OVER 25 YEARS, THE VACTAGON DRUM TOP VACUUM FROM INDUSTRIAL VACUUM HAS SET THE STANDARD FOR POWER, DURABILITY CONVENIENCE AND EFFECTIVENESS.

USER-FRIENDLY & ADAPTABLE

THE VACTAGON DRUM TOP VACUUM HAS BEEN USED FOR LEAD PAINT REMOVAL ON THE CAPITOL BUILDING IN WASHINGTON, THE BROOKLYN BRIDGE, BY NASA, UTILITIES INCLUDING TVA, THE MILITARY AND PRIVATE INDUSTRY FOR ALL TYPES OF PLANT MAINTENANCE.

IDEAL FOR ASBESTOS, LEAD AND OTHER SENSITIVE MATERIAL CLEAN UP.

EXCLUSIVE DUAL PRE-FILTRATION

A DOUBLE STAGE, TWO-CARTRIDGE FILTER SYSTEM DESIGN THAT IS EASILY CLEANED OR CHANGED TO PROTECT THE OPTIONAL FINAL HEPA FILTERING STAGE FOR MAXIMUM VACUUM POWER WITH SIMPLE MAINTENANCE.

EACH HEPA FILTER IS RATED AT 99.97% EFFICIENCY AT 0.3 MICRONS AND MEETS OR EXCEEDS OSHA AND CLEAN AIR ACT STANDARDS.

INCLUDES A TEN-FOOT VACUUM HOSE, 54 INCH WAND AND FLOOR TOOL.

AVAILABLE IN SINGLE, DOUBLE OR QUAD-MOTOR CONFIGURATIONS.

AVAILABLE IN ELECTRIC OR PNEUMATIC MODELS. WET OR DRY OPERATION STANDARD.



DRUM TOP VAC ELECTRIC MODELS



SINGLE-MOTOR VACUUM DT55



SINGLE-MOTOR VACUUM WITH FINAL HEPA FILTER & WATER SHUT-OFF FLOAT DT55H



TWIN-MOTOR VACUUM DT255



TWIN-MOTOR VACUUM WITH FINAL HEPA FILTER DT255H

FEATURES & OPTIONS

DURABLE POWDER-COAT FINISH
OPTIONAL HEPA FILTRATION
OPTIONAL WATER SHUT-OFF SYSTEM
ATTACHMENTS & ACCESSORIES

Electric	Power	Air Flow	Inches of Hg	Filtration	Float	Inlet Size
DT55	110V~120V, 9amp	106 CFM	6.5"	STD	NO	1.5" or 2"
DT55F	110V~120V, 9amp	106 CFM	6.5"	STD	YES	1.5" or 2"
DT55H	110V~120V, 9amp	106 CFM	6.5"	HEPA	NO	1.5" or 2"
DT55HF	110V~120V, 9amp	106 CFM	6.5"	HEPA	YES	1.5" or 2"
DT255	110V~120V, 16amp	211 CFM	6.5"	STD	NO	1.5" or 2"
DT255F	110V~120V, 16amp	211 CFM	6.5"	STD	YES	1.5" or 2"
DT255H	110V~120V, 16amp	211 CFM	6.5"	HEPA	NO	1.5" or 2"
DT255HF	110V~120V, 16amp	211 CFM	6.5"	HEPA	YES	1.5" or 2"



